

## ATV MOWER, 120, WITH FLAP, 15 HP

35-VKMATV120H



### Flail mower with flap for increased speed and versatile handling

- Flail mower with hammer flails for ATV
- Working width 120 cm
- Fit wheels for stability and compliance at the sides or for maximum accessibility at the back
- The wheels are mounted behind or at the side of the machine, either behind for maximum access close to obstacles or at the side for stability and enable it to follow ground contours
- Sturdy rubber balloon wheels (16-6.50x8)
- The wheels are individually height adjustable with spring-locked crank to prevent the crank moving backwards as a result of vibration
- The angle of penetration is adjusted with a turnbuckle under the tow bar
- Skids at the sides for stable, smooth operation
- Mudguard at the front to reduce the risk of stone chipping
- 15 hp engine with oil level monitor
- Laser cut plate handles for longer durability

#### TECHNICAL DATA

Working width	1200 mm
Engine Power	15 hp
Cutting height,	Max: 300 Min: 20 mm
Operating speed	6 - 12 km/h
L x W x H	1800 x 1850 x 830 mm
Flails	28
Weight	243 kg

### Why should you choose this pasture topper?

- Fitted with a flap at the back, which releases the grass to avoid excessive accumulation under the hood. In this way you save on fuel and reduce wear on the belts. You can also operate at a higher speed than an ATV flail mower without a flap. The grass is also spread more evenly.
- Deals with tougher vegetation where there may be ground obstacles such as tussocks and roots
- Many of our customers use it for topping pastures, parks and roadsides
- Stable construction

### A flail mower built for a long service life, so that you can spend your money on something else

- Grease nipples on support and rotor roller bearings
- Sealed cover over the belts
- The whole construction is well-protected but easy to access for cleaning, servicing and repair
- Wide support roller at the rear
- The tow bar has five fixed lateral adjustments
- The flap at the back opens with two plate handles on each side

### Tips for use

For best results, and a longer service life for belts, we recommend mowing at a speed of 10 km/h if the grass is of normal height. For higher grass, raise the mower to its maximum and mow twice.

### Assembly & delivery

Delivered to the dealer of your choice in a steel crate box who can arrange delivery to your address at an additional cost if required.

## ACCESSORIES

Extend your application with these practical accessories.

**35-PDVKMATV**  
**23-DH**

Sideshift adjustment tow bar  
Dolly manual