

FEEDER WITH DIAGONAL BARRIER FOR CATTLE, 12 FEED OPENINGS

34-FHD









Using the feeder offers savings on feed, excellent hygiene and healthier animals!

- 12 feed openings
- Diagonal barrier
- 3 base supports provide good stability
- Adjustable roof height
- Fork lift insertion points for movement of feeder

The sturdy diagonal barrier made of 42 mm tubing and 437 mm wide feed openings is the strongest feed barrier available without moving parts. All sides can be opened, and when filling with feed one of the sides can be opened to drop in the feed.

The roof is height-adjustable to offer the best feed protection, it is also fitted as standard with a protection arch all the way around the roof to prevent injury to the animals. The feeder is very stable due to the three base supports. It has fork lift insertion points to make it easy to move the feeder.

The entire feeder is galvanised for a long service life.

NOTE! Any plastic film/netting around the hay bale must be removed before use.

More benefits of using our feeder:

- Reduction in feed waste
- Improved hygiene at the feeder
- Less feed is required as it is not trampled on or not eaten by the animals

Please consider your livestock and their needs when choosing a feeder. Always follow your country's agricultural rules and animal welfare regulations.

Accessories

Extend your application with these practical accessories.

28-333340AM Ground-reinforcing plastic mat **47-1321604** Netting for bales **47-1321606** Hay net hanging

TECHNICAL DATA

Feed openings 14 pcs

L x W x H 2000 x 2000 x 2700 mm

Pipe dimension 43 mm
Weight 310 kg