

CHIPPER 170, HYDRAULIC INFEED WITH PUMP AND TANK

13-WC17H2



Hydraulically fed chipper with high capacity

- Double infeed rollers
- Easy infeed speed control
- Double branch crushers
- Wood dimensions up to 17.5 cm. Boards and bushes to a width of 31 cm.
- Own hydraulic system with tank and PTO-operated pump
- Hydraulic infeed in four positions: stop, forwards, backwards and stop
- Emptying flap at the base – for cleaning and maintenance
- Transport mode that makes your transport operations safer and takes up less storage space
- Adjustable infeed speed
- Deep infeed hopper with stop lever
- Good accessibility for easy maintenance
- EN 13525:2020 approved
- 20 litre-can of hydraulic oil included
- PTO shaft with shear bolt supplied as standard

Own hydraulic system with tank and PTO-operated pump

Kellfri's WC17H Chipper for wood dimensions up to 17.5 cm, with heavy-duty cutting disc, hydraulic feeder rollers, pump and tank.

The chipper, with its own hydraulic system, is ideal for operation with both PTO 540 rpm

TECHNICAL DATA

Wheel drive	Direct, PTO shaft with shear bolt
Engine power	60-70 hp
Hydraulic flow	13-27 l/min
Hydraulic oil tank	24 l
Infeed measurement	178 x 310 mm
Feed method	Double infeed motors
Large pulley	180 mm
Small pulley	120 mm
Infeed hopper next	180 x 310 mm (drive rollers)
Infeed hopper	660 x 700 mm (opening)
Capacity	Timber ø 17,5 cm
3-point connection	Cat. 1 & 2
Rpm	540/1000 rpm
Weight	560 kg

The hydraulic system means that the chipper's valves and system are not overloaded, regardless of your tractor's rpm. Depending on the type of wood and materials to be chipped it can be a good idea, for the best chipping performance and capacity, to use as high a speed as possible. PTO 540 rpm is the minimum speed for good chipping, and the maximum speed is 1000 rpm.

If the logs and branches are wet, you should delimb most of the branches before using the chipper. If the material is dry, just go ahead and use it without delimbing. The chipper is fitted with a removable branch crusher as standard.

Adjustable infeed speed, powerful bearings, forward/reverse feeder roller functionality and deep infeed hopper for safe machine feeding.

Adjustable discharge chute and ejection angle adjustment for even spreading or exact trailer filling.

Sturdy cutting disc with holes for maximum safety

Rejäl huggskiva med hål för att kunna låsa den vid underhåll och för maximal säkerhet. Kvistbrytare för maximalt resultat vid flisning av träd med grenar. På huggskivan finns det 4 st knivar med dubbla skärsidor som är härdade. Flisuggen har ett ställbart motstål för önskad flisstorlek.

För maximal kontroll, funktion och säkerhet sker inmatningen med manöverspak, stopp, framåt, bakåt och stopp.

Utkastningsröret är uppdimensionerat och har en innerdimension på 18 cm.