

ATV FLAIL MOWER WITH FLAP, 1.2 M, Briggs and Stratton 13.5 HP

35-VKMATV120H.B



Flail mower with flap for increased speed and versatile handling

- 13,5 hp Briggs and Stratton engine
- Working width 120 cm
- Fit wheels for stability and compliance at the sides or for maximum accessibility at the back
- Sturdy rubber balloon wheels (16-6.50x8)
- The wheels are individually height adjustable with spring-locked crank to prevent the crank moving backwards as a result of vibration
- The angle of penetration is adjusted with a turnbuckle under the tow bar
- Skids at the sides for stable, smooth operation
- Mudguard at the front to reduce the risk of stone chipping

TECHNICAL DATA

Working width 1200 mm **Engine power** 13,5 hk

Cutting height Max: 300 mm Min: 20 mm

Operating feed 6 - 12 km/h

Engine Briggs & Stratton 13.5 hk LxWxH 1800 x 1850 x 830 mm

Flails 28 pcs Weight 243 kg

- Why should you choose this pasture topper?

 Fitted with a flap at the back, which releases the grass to avoid excessive accumulation under the hood. In this way you save on fuel and reduce wear on the belts. You can also operate at a higher speed than an ATV flail mower without a flap. The grass is also spread more evenly.
- Deals with tougher vegetation where there may be ground obstacles such as stones, tussocks and roots
- Many of our customers use it for topping pastures, parks and roadsides
- Stable construction

A flail mower built for a long service life, so that you can spend your money on something else

- Grease nipples on support and rotor roller bearings
- Sealed cover over the belts
- The whole construction is well-protected but easy to access for cleaning, servicing and repair
- Wide support roller at the rear
- The tow bar has three fixed lateral adjustments

For best results, and a longer service life for belts, we recommend mowing at a speed of 10 km/h if the grass is of normal height. For higher grass, raise the mower to its maximum and mow twice.

Assembly & delivery

Delivered to the dealer of your choice in a steel crate box who can arrange delivery to your address at an additional cost if required.

AccessoriesExtend your application with these practical accessories

35-PDVKMATV 23-DH

Sideshift adjustment tow bar

Dolly manual

R35-VKMATV.103 R35-VKMATV.115 Spacer for Hammer flail Heavy for ATV mower Sleeve between y-flails 14 x 22 x 17 mm