

TIPPING TRAILER ATV 1,420 KG WITH ELECTRICAL HYDRAULIC TIPPER

23-TV10H









See videos

ATV trailer with electrical hydraulic tipper and powerful three-stage tipper ram

- Electrical hydraulic tipper 12 V
- Sturdy floor in 2 mm tread plate
- Powerful three-stage tipper ram
- All-round tyres 22 x 11 10
- Small storage box for control box included

Our tipping trailer is manufactured from durable, hard-wearing tread plate, galvanised for a long service life.

The ideal trailer for loading gravel, earth, chippings, grass, leaves or other material. This is a transport trailer made for efficient transportation of material, regardless of whether you have a large garden tractor, ATV or small tractor.

The carefully thought-out design and generously-dimensioned floor allow you to transport large volumes both with and without extension sides. With a trailer for all environments, you will be able to get around on smooth tracks and asphalt or off-road and in the forest.

The chassis frame is constructed with 40 x 80 mm profiles with a thickness of 2.75 mm, making the trailer stable under heavy loads.

FOUNDAL DATA

TECHNICAL DATA	
Axle type	Bogie
Floor dimension	2000 x 1070 x 580 mm
Wheels	22 x 11 - 10
LxWxH	3450 x 1250 x 1100 mm
Max. load	1420 kg
Tip	El - hydraulic, 12 V
Weight	290 kg

Openable headboard and tailgate

The headboard can be opened downwards or removed with two clamps and hinges. A removable headboard/flap is useful when you want to use the trailer to carry longer loads such as logs or beams.

The tailgate is designed to be easily opened or lowered so that it acts as a ramp. The flap has two downward hinges to enable material to be pulled up on it. The tailgate can also be locked at the top edge for use as a spreading hinge. A spreading hinge is useful when you want to tip gravel out over a longer distance in an even flow, for example for spreading gravel on tracks or driveways. The tailgate includes variable brackets at the top edge for spreading gravel. The angle of the flap opening is adjusted with the aid of the associated links. The trailer is ideally designed for spreading gravel and sand on your tracks.

The 22x11-10 tyres, together with the trailer's chassis, give good ground clearance, and the tyre dimensions mean that the trailer rolls easily. The tyre pattern works well on grass, gravel and asphalted roads.

Stabilisers without wheels with crank and 50 mm rotatable tow bar ball hitch included.

The tailgate in some of the illustrations is equipped with a quick lock. This is an accessory.

The tipping trailer requires assembly.

Accessories

Extend your application with these practical accessories.

23-TV10HBB2 Battery box **23-TV10HJS** Stabilisers with wheels

23-DH Dolly manual 23-TV10HFL Extension side

R23-TV10H.019 Quick release spring latch