

GRITTER, 1.3 M INCL. CYLINDER AND HOSE

32-S350C



[Se videos](#)

Tractor-mounted gritter with hopper volume of 350 l

- 1,3 m working width
- 350 l hopper volume
- Equipped with hydraulic cylinder as standard – Self-loading
- Robust design
- Spring-loaded bottom flaps – Dependable
- Variable output – Saves money and offers good results
- Equipped with agitator – Prevents clumps
- Quick-emptying function
- Three-point linkage

Kellfri's tractor-mounted gritters have a wide range of applications. The gritter is suitable for both ice clearing using various materials as well as the laying of sawdust and chippings in running tracks or similar or for top dressing green areas.

With self-loading kit as standard, including hydraulic cylinder and hoses, allowing the gritter to self-load straight from the pile. When tractor-mounted, loading is easily and efficiently managed from the tractor's control panel by hydraulically angling the gritter backward. In the lowered position, reverse into the sand pile, lift the gritter back to the working position and the hopper will be filled ready for spreading to commence.

Hydraulic output and agitator with variable speed saves money and offers good results on all surfaces, spring-loaded bottom flaps allow gritting of uneven areas and trouble-free operation.

Robust design, thought-out components and several different working widths.

The gritter requires a single-acting, return and double-acting hydraulic outlet on the tractor. The gritter is supplied with two hydraulic ½ inch, quick coupling male hoses and three-point linkage.

TECHNICAL DATA

Working width	1300 mm
Hopper volume	350 l
Spring loaded bottom flaps	Standard
Hyd. operation	Standard
Mixer	Standard
Self-loading	Standard
Variable out feed	Standard
Support legs	Standard
Total width	1450 mm
Weight	322 kg