

Farming made easy.

ATV Mower, FRONT MOUNTED

35-VKMATVF









Front mounted flail mower for larger ATVs!

- Powered by centrifugal clutch
- Working width 100 cm
- Standard side shift
- 44 Y-flails
- Adjustable mounting plate

In distinction from a flail mower that is rear mounted, with a front mounted flail mower for your ATV you can see what and where you are cutting, and thus reduce the risk of driving over material that can damage the machine. Working width 100 cm.

A major advantage of a front mounted flail mower is that you minimise compressed grass, as the flail mower reaches the grass before you drive over it yourself with your ATV. This makes cutting more effective.

Moreover, our front mounted flail mower is supplied with side shift adjustment as standard, which enables you to set the flail mower on the left or the right. Positioning the flail mower on the right or the left enables you to simply access fences, trees and posts. The mower is driven by a centrifugal clutch, which provides a gentle and effective power transmission from the motor to the rotor.

As the flail mower is front mounted and adapted for ATVs, you access places that wouldn't normally be possible with a large, rear mounted flail mower. Transporting the flail mower is also simpler thanks to its practical size and weight.

Kellfri's front mounted flail mower is supplied with 44 Y-flails which break the grass. Y-flails are also ideal for occasions when you need to cut coarser material such as brushwood for example.

Our front mounted flail mower for ATVs is an excellent alternative if you want to quickly get started on your work. The flail mower is suitable for tasks including cutting pastures, clearing brushwood and mowing grass.

The flail mower is supplied with an adjustable mounting plate. Universal attachment for fixed mounting to ATVs is not included, see **accessories**.

Accessories

Extend your application with these practical accessories.

35-UNIFVKMATV Universal attachment

TECHNICAL DATA

Working width 1000 mm

Engine Power 15 hp

Belts 2 pcs BX38

Cutting height Max: 80 mm Min: 20 mm

L x W x H 1830 x 1240 x 770 mm

Engine Gasoline

Flails Y-flails 22 set (44 pcs)

Vikt 158 ka