

WHEELED GRASS TRIMMER

27-FT351



[See videos](#)

Get great results fast by using a powerful wheeled trimmer

- Simple to operate, thanks to its large wheels
- Adjustable cutting height 38 - 76 mm
- Euro 5 engine
- Petrol-driven, single-cylinder 4-stroke
- Cutting width 546 mm

A valued tool on many farms

A wheeled grass trimmer which helps you tidy up the places you can't reach with your lawn mower. A welcome tool on many farms, in stables, property management services, gardens and parks.

Trim alongside buildings, under regular and electric fences, around posts and trees. There is a long list of areas where saplings and other unwanted vegetation grows. Kellfri's grass trimmer, with its narrow, high wheels can be used in tougher environments, as the wheels smoothly compensate for irregularities in the surface.

Ergonomic design

A wheeled grass trimmer is a unique combination of lawn mower and trimmer. Compared with a regular string trimmer, this wheeled trimmer is much gentler on your back and spinal discs. It's also more powerful than the great majority of string trimmers on the market.

Use

The cutting height is simple to adjust so that you can adapt it to your particular terrain. The trimmer is operated by means of the handle, where the coupling and safety bar are also located. The safety bar, also known as the dead man's grip, must be pressed down in order for the grass trimmer to be operated.

This is for reasons of safety. With a cutting width of 546 mm covered by a side guard, it clears grassy areas efficiently, ergonomically and safely. View the video in which one of our previous models shows how the grass trimmer works efficiently in a number of different areas. The model shown here has been updated with performance improvements such as the new Stage 5 engine.

The trimmer wire is easy to replace by fixing with a clamp. Always follow the safety and operating instructions and use common sense. It will give you many years of pleasure from using your grass trimmer.

TECHNICAL DATA

Power	3,2 W
Cutting width	546 mm
Cutting height	38 - 76 mm
Max slope	15°
Engine, Euro 5	1 cylinder 4-stroke- petrol-driven
Oil tank	0,5 l
Oil typ	API SG-SL 10W-30
Spark plug gap	0,7 - 0,8 mm
Weight	28,5 kg