

## PALLET FORK 1.5 TONNES, SUITABLE FOR TRIMA

16-JPF2T15



[See videos](#)

**Mechanically adjustable pallet fork in new updated version with FEM suspension and new design on the pallet fork frame for better working visibility**

- Fork length 1,200 mm
- Frame width 1,200 mm
- Mechanically adjustable forks
- Attachment which fits Trima
- Max. weight 1.5 tonnes
- Type FEM II A suspension

The market's most affordable mechanical pallet fork in a new, updated version according to the industry standard.

CE marked and manufactured to the highest quality and supplied complete with fork arms and FEM II A suspension.

The pallet fork rack's forks are adjustable and have a fork length of 1.2 m, which allows you to lift an EU pallet lengthwise. Max. load 1.5 tonnes Supplied with attachment that fits Trima

### **Stable and flexible lifting equipment on both large and small farms**

A stable pallet fork with a powerful design, extra long forks for a high lifting capacity suitable for many different tasks. This 1.5 tonne pallet fork has laser cut attachments, ideal for front loaders and smaller wheel loaders.

Kellfri's mechanical pallet fork has been developed to provide full control and a good view both when loading and unloading, thanks to the new design of the frame.

All Kellfri's pallet forks/fork racks are CE marked and manufactured to the highest quality and supplied with fork arms and FEM II A suspension.

### **Adjustable pallet forks**

The pallet fork's forks are manually adjustable. To adjust the width, move the forks to the current position. The fork rack has pre-selected positions at intervals of 10 cm.

You can easily lock the fork position by using the latch on the top.

Avoid uneven horizontal load distribution for best stability.

### TECHNICAL DATA

Type	FEM II A
Maxload	1500 kg
Pallet fork frame width	1200 mm
Pallet fork frame height	407 mm
Pallet fork width	100 mm
Pallet fork length	1200 mm
Pallet fork thickness	30 mm
Weight	148 kg