

VERGE FLAIL MOWER W 1.45 m, LIGHTWEIGHT

35-WKS145



[See videos 1.](#)

[See videos 2.](#)

Lightweight verge flail mower with working width of 1.45 m for smaller tractors

- **Support roller for correct cutting height**
- **Practical for smaller tractors of 25-45 hp**
- **24 hammer flails**
- **Tiltable cutting head**
- **Low weight of 270 kg**

With its low weight and working width of 1.45 m, our WKS145 verge flail mower is ideal for smaller tractors of 25-45 hp. By means of the side shift adjustment, the verge flail mower can be adjusted for work either behind the tractor or variably at the side. You can easily cut ditch edges, median strips on roads and other places that are difficult to reach.

The verge flail mower has a tiltable cutting head and can be angled 90° upwards and 50° downwards laterally, which makes it very flexible. This makes the machine particularly suitable for cutting and topping ditch edges, but it works equally well on level areas and hedges.

The mower has a fine-toothed welded counter bar in the chassis to break up the material more effectively.

Support roller and 24 hammer flails

The front of the verge flail mower is fitted with steel plates that adapt to the substrate and protect both the tractor and the surroundings from stone chipping and grass spray. The support roller has a scraping iron to keep the roller free from cut material.

The verge flail mower is fitted as standard with hammer flails. There are 24 flails in total, ensuring that the grass is broken up. The mower is also adapted for Y-flails, which can be purchased additionally (not included).

Hydraulic side shift adjustment and tiltable cutting head

The verge flail mower's chassis is made of 3 mm thick steel, and the side plate is 6 mm thick. The machine's cutting head can be angled 90° upwards and 50° downwards. High level of safety with collision protection that angles the machine upwards if you hit a stump, for example. The verge flail mower is supplied with PTO drive shaft, transmission oil and hydraulic hoses as standard.

The mower requires two double-acting hydraulic outlets on the tractor. The verge flail mower is supplied with four hydraulic ½ inch, quick coupling male hoses.

TECHNICAL DATA

Working width	1450 mm
Chassis	3/6 mm steel
Engine Power	25-45 hp
Colour	Green
Belts	3 pcs BX51 Li1295
L x W x H	1560 x 690 x 530 mm
Rotor roller	108 mm ø, thickness 8 mm
Side shift	Hydraulic
Flails	24 pcs hammer flails
Sly diameter	Max 25 mm
Support roller	95 mm ø
3-point linkage	Cat 1
PTO speed	540 rpm
Rotor speed	2295 r/min at 540 rpm
Weight	307 kg